

DC-DC ПРЕОБРАЗОВАТЕЛИ «PEAK»

Наименование	P _{вых} , Вт	U _{вх} , В	U _{вых} , В/U _{вых} ,мА	Прочность изоляции, В	Размеры корпуса, мм	Рабочий температурный диапазон, °С
P6CU-0505ELF	1	4.5-5.5	5/200	1000	19.5x6x9.5	-40...+85
P6CU-1212E DC-DC	1	10.8-13.2	12/84	1000	19.5x6x9.5	-40...+85
P6CU-1212Z DC-DC	1	10.8-13.2	+/-12/ +/-42	1000	19.5x6x9.5	-40...+85
PSD-0505SLF	1	4.5-5.5	5/200	1000	-	-40...+85
P6CU-2405Z,DC/DCконвер.	1	21.6-26.4	+/-5/ +/-100	1000	19.5x6x9.5	-40...+85
P6CU-0505Z,DC/DCконвер.	1	4.5-5.5	+/-5/ +/-100	1000	19.5x6x9.5	-40...+85
P6CU-0505E,DC/DC конвертер	1	4.5-5.5	5/200	1000	19.5x6x9.5	-40...+85
P6LU-1212E,DC/DC конвертер	1	10.8-13.2	12/84	3000	19.5x6x9.5	-40...+85
PSD-1205S, DC-DC конв. SMD	1	10.8-13.2	5/200	1000	-	-40...+85
PSD-0512D, DC-DC конв.	1	4.5-5.5	+/-12/ +/-50	1000	-	-40...+85

