



SPECIFICATIONS

Basic Functions		Range	Best Accuracy
Wind Speed Measurement		2-10m/s 10-30m/s	± (3%+5dig) ± (3%+8dig)
Wind Count Measurement (CMM)		0.001~9999x100	✓
Wind Count Measurement (CFM)		0.001~9999x100	✓
Temperature Measurement	The Temperature of Mainframe	0~40°C 32~113°F	± 3°C ± 4°C
Temperature Measurement	The Temperature of Transducer	0~40°C 16~122°F	± 3°C ± 4°C
Special Functions			
Data Hold		Display "H"	✓
Wind Speed/Wind Count Display		Display "VEL/FLOW"	✓
Max / Min Mode		Display "Max" or "2/3 Max"	✓
Sleep Mode		Around 10 Minutes	✓
Working Temperature	The Temperature of Mainframe	0~40°C	✓
Working Temperature	The Temperature of Transducer	0~40°C	✓
Deposited Temperature		-10~55°C(14°F~122°F)	✓
Low Battery Display		<7.2V	✓
Relative Humidity		≤7.5%	✓
USB			✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery x 1
LCD Size	57 x 37mm
Product Colour	Red and Grey
Product Net Weight	375g
Product Size	162 x 78 x 30mm
Standard Accessories	English Manual, Carrying Bag, USB Interface Cable, CD
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	530 x 420 x 365mm (0.081 CBM Per Standard Carton)
Standard Carton Gross Weight	21kg