

Multi-function Digital Multimeters



MS8236 Network Multimeters

Function	Range	Accuracy
DC Voltage	200mV/2V/20V/200V/600V	(0.7%rdg+3dgt)
AC voltage	200mV/2V/20V/200V/600V	(0.8%rdg+5dgt)
DC Current	200uA/2000uA/20mA/200mA 2A/10A	(1.2%rdg+5dgt) (2.0%rdg+5dgt)
AC Current	200uA/2000uA/20mA/200mA 2A/10A	(1.5%rdg+5dgt) (3.0%rdg+5dgt)
Resistance	200 Ω /2K/20K/200K/2M/20M	(1.0%rdg+3dgt)
Features		
Conformance to IEC61010-1 CAT III 600V		
Display	1999 Counts	
Diode Check	✓	
Continuity Check	✓	
Auto range and manual range	✓	
Data Hold	✓	
MAX value measurement	✓	
Back Light	✓	
Phone Check	Identify the state in the working telephone line: Busy, Ringing or Clear.	
Tone	Judge continuity of the cables or wires. Track the cables or wires, and diagnose the break point.	
NetCable Check	Test for open circuits, shorts, miswires, reversals, split pairs and LCD display the test result. SHIELD detection tests a cable's shield integrity. Main unit and one remote allow one person testing of T568A, T568B, 10Base-T. Easy to read fault display and high speed testing. Debug mode for detailed fault identification results.	
Low Battery indication	✓	
Auto power off	✓	
None Contact Voltage Detect	✓	
Power Supply	9V(6F22)	
Dimension	186(L) × 88(W) × 55(H)mm	
Weight	Appro×400g	

