


Features

- ◆ Wide 2:1 input range
- ◆ Full SMD-design
- ◆ High efficiency up to 86%
- ◆ Extended operating temperature range -40°C to 85°C
- ◆ I/O isolation 1'500 VDC
- ◆ Indefinite short circuit protection
- ◆ Input filter to meet EN 55022, Class A and FCC, level A without external components
- ◆ Shielded metal case with insulated baseplate
- ◆ 24-pin DIP with industry standard pinout
- ◆ High reliability, MTBF >1 Mio. h
- ◆ 3-year product warranty



The TEN 5 Series is a range of DC/DC-converter modules with wide input range of 2:1. State of the art SMD-technology guarantees a product with very high reliability and good cost /performance ratio. High efficiency allows an operating temperature range of -40°C to $+85^{\circ}\text{C}$. I/O-isolation of 1'500 VDC together with conducted noise compliance to EN 55022-A and FCC, level A makes these converters ideal for a wide range of applications in communications, mobile battery powered equipments and industrial systems.

Models

Ordercode	Input voltage range	Output voltage	Output current max.	Efficiency typ.
TEN 5-0510	4.5 – 7 VDC (5 VDC nominal)	3.3 VDC	1200 mA	75 %
TEN 5-0511		5 VDC	1000 mA	79 %
TEN 5-0512		12 VDC	500 mA	82 %
TEN 5-0513		15 VDC	400 mA	82 %
TEN 5-0521		± 5 VDC	± 500 mA	79 %
TEN 5-0522		± 12 VDC	± 250 mA	82 %
TEN 5-0523		± 15 VDC	± 200 mA	82 %
TEN 5-1210		9 – 18 VDC (12 VDC nominal)	3.3 VDC	1200 mA
TEN 5-1211	5 VDC		1000 mA	81 %
TEN 5-1212	12 VDC		500 mA	84 %
TEN 5-1213	15 VDC		400 mA	84 %
TEN 5-1221	± 5 VDC		± 500 mA	81 %
TEN 5-1222	± 12 VDC		± 250 mA	84 %
TEN 5-1223	± 15 VDC		± 200 mA	84 %
TEN 5-2410	18 – 36 VDC (24 VDC nominal)		3.3 VDC	1200 mA
TEN 5-2411		5 VDC	1000 mA	83 %
TEN 5-2412		12 VDC	500 mA	86 %
TEN 5-2413		15 VDC	400 mA	86 %
TEN 5-2421		± 5 VDC	± 500 mA	83 %
TEN 5-2422		± 12 VDC	± 250 mA	86 %
TEN 5-2423		± 15 VDC	± 200 mA	86 %
TEN 5-4810		36 – 75 VDC (48 VDC nominal)	3.3 VDC	1200 mA
TEN 5-4811	5 VDC		1000 mA	83 %
TEN 5-4812	12 VDC		500 mA	86 %
TEN 5-4813	15 VDC		400 mA	86 %
TEN 5-4821	± 5 VDC		± 500 mA	83 %
TEN 5-4822	± 12 VDC		± 250 mA	86 %
TEN 5-4823	± 15 VDC		± 200 mA	86 %

Input Specifications

Input current no load / full load	5 Vin models: 50 mA / 1460 mA typ. 12 Vin models: 20 mA / 590 mA typ. 24 Vin models: 5 mA / 290 mA typ. 48 Vin models: 3 mA / 145 mA typ.
Start-up voltage / under voltage shut down	5 Vin models: 4.4 VDC / 4.0 VDC 12 Vin models: 8.0 VDC / 8.0 VDC 24 Vin models: 16.0 VDC / 16.0 VDC 48 Vin models: 32.0 VDC / 32.0 VDC
Surge voltage (1 sec. max.)	5 Vin models: 10 V max. 12 Vin models: 25 V max. 24 Vin models: 50 V max. 48 Vin models: 100 V max.
Reverse voltage protection	1.0 A max.
Conducted noise (input)	EN 55022 level A, FCC part 15, level A

Output Specifications

Voltage set accuracy	1.0 %
Regulation	<ul style="list-style-type: none"> - Input variation Vin min. to Vin max. 0.3 % max. - Load variation 20 – 100 % <li style="padding-left: 150px;">single output models: 1.0 % max. <li style="padding-left: 150px;">dual output models balanced load: 2.0 % max. <li style="padding-left: 150px;">dual output models unbalanced load: 5.0 % max.
Ripple and noise (20 MHz Bandwidth)	50 mVpk-pk max.
Temperature coefficient	±0.02 %/K
Output current limitation	>120 % of I _{out} max., constant current
Short-circuit protection	indefinite (automatic recovery)
Capacitive load	<ul style="list-style-type: none"> single output models: 6800 µF max. dual output models: 1000 µF max. (each output)

General Specifications


Temperature ranges	<ul style="list-style-type: none"> - Operating -40°C to +85°C - Case temperature +100°C max. - Storage -55°C to +125°C
Derating	3.5 %/K above 70°C
Humidity (non condensing)	95 % rel H max.
Reliability, calculated MTBF (MIL-HDBK-217F, @ +25°C, ground benign)	>1 Mio. h
Isolation voltage (60 sec) - Input/Output	1'500 VDC
Isolation capacity - Input/Output	380 pF typ.
Isolation resistance - Input/Output	>1'000 M Ohm (500 VDC)
Switching frequency	300 kHz typ. (Pulse frequency modulation PFM)
Safety standards	UL 60950-1, IEC/EN 60950-1
Safety approval	CSA File No. 226037 http://directories.csa-international.org

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

Physical Specifications

Casing material	steel, nickel plated
Baseplate material	non conductive FR4
Potting material	epoxy (UL 94V-0 rated)
Weight	16.9 g (0.59 oz)
Soldering temperature	max. 265°C / 10 sec.

Outline Dimensions mm (inches)



Pin-Out		
Pin	Single	Dual
2	-Vin (GND)	-Vin (GND)
3	-Vin (GND)	-Vin (GND)
9	No pin	Common
11	No con.	-Vout
14	+Vout	+Vout
16	-Vout	Common
22	+Vin (Vcc)	+Vin (Vcc)
23	+Vin (Vcc)	+Vin (Vcc)

Pin diameter $\varnothing 0.5 \pm 0.05$ (0.02 ± 0.002)
Tolerances ± 0.5 (± 0.02)

Specifications can be changed any time without notice